

### Remarks

In view of the above amendments and the following remarks, reconsideration and further examination are requested.

The specification and abstract have been reviewed and revised to make a number of editorial revisions. A substitute specification and abstract have been prepared and are submitted herewith. No new matter has been added. Enclosed is a marked-up copy of the specification and abstract indicating the changes incorporated therein.

Claims 1-13 have been rejected under 35 U.S.C. § 112, first paragraph, as not being properly enabled. Specifically, the rejection indicates that the phrase "any one of the triangles" in claims 1, 7 and 10 means that each of the triangles shares at least one edge with all other triangles included in the same partial polygon and that this is not supported by the specification. Based on this rejection, it appears that the Examiner is incorrectly construing the intended meaning of this phrase. As a result, claims 1, 7 and 10 have been amended so as to change this phrase to "at least one other triangle" which is clearly supported by Figures 7A and 8A. Therefore, withdrawal of the rejection under 35 U.S.C. § 112, first paragraph, is respectfully requested.

The drawings have been objected to under 37 C.F.R. 1.83(a) as not showing every feature of the invention specified in the claims. It is apparent that the above-discussed amendment to claims 1, 7 and 10 should also overcome this objection to the drawings. As a result, withdrawal of the objection is respectfully requested.


In addition, claims 1-13 have been amended to make a number editorial revisions. These revisions have been made to place the claims in better U.S. form. None of these amendments have been made to narrow the scope of protection of the claims, nor to address issues related to patentability and therefore, these amendments should not be construed as limiting the scope of equivalents of the claimed features offered by the Doctrine the of Equivalents.

In view of the above amendments and remarks, it is submitted that the present application is now in condition for allowance. The Examiner is invited to contact the undersigned by telephone if it is felt that there are issues remaining which must be resolved before allowance of the application.

Respectfully submitted,

Keiichi SENDA et al.

By:

  
David M. Ovedovitz  
Registration No. 45,336  
Attorney for Applicants

DMO/jmj  
Washington, D.C. 20006-1021  
Telephone (202) 721-8200  
Facsimile (202) 721-8250  
March 30, 2004

TITLE OF THE INVENTION

POLYGON RENDERING DEVICE

BACKGROUND OF THE INVENTION

5 Field of the Invention

[0001] The present invention relates to rendering devices and, more specifically, to rendering devices which go through a rendering process of generating image data representing polygons for display on display devices.

10

Description of the Background Art

[0002] ~~Such a rendering process is~~ Rendering processes are found in many documents, e.g., Yamaguchi, Fujio: A Unified Approach to Interference Problems Using a Triangle Processor, Proceeding of SIGGRAPH '85, July 1985. FIG. 11 is a block diagram showing the basic structure of a conventional rendering device *CUrend*. The rendering device *CUrend* of FIG. 11 includes a polygon data storage section 701, a concave polygon determination section 702, a first triangulate section 703, a second triangulate section 704, a triangle rendering section 705, and a display section 706.

[0003] Described below is the operation of such a conventional rendering device *CUrend*. The polygon data storage section 701 stores several pieces of polygon data *Dpoly*. One piece of polygon data *Dpoly* ~~at least~~ includes at least *n* (where *n* is a natural number of 3 or larger) sets of vertex coordinates *P1* to *Pn* so that a polygon

*P* is rendered. Here, the vertex coordinates *P1* to *Pn* are two-dimensional (2D) or three-dimensional (3D) coordinates. If being 3D coordinates, all of the vertex coordinates *P1* to *Pn* need to be located on a single plane. The polygon data *Dpoly* sometimes  
5 accompany various other information together with the vertex coordinates *P1* to *Pn*. Such additional information will be described later as appropriate.

[0004] The concave polygon determination section 702 receives the polygon data *Dpoly* from the polygon data storage section 701.  
10 In the case that the vertex coordinates *P1* to *Pn* included in the polygon data *Dpoly* are 3D, a similarity transformation process is applied onto a predetermined 2D plane (hereinafter, *xy* plane) *Ft*.

[0005] Assuming now that the polygon data *Dpoly* includes *n* sets  
15 of vertex coordinates describing the polygon *P*, i.e., *P1* (*x1*, *y1*, *z1*), *P2*(*x2*, *y2*, *z2*), ..., *Pn*(*xn*, *yn*, *zn*). In the similarity transformation process, the concave polygon determination section 702 first calculates a normal vector *N* to the polygon *P*. If the derived normal vector *N* is parallel to the *z*-axis, every *z* coordinate  
20 of the vertex coordinates *P1* to *Pn* is changed in value to 0. The resultant vertex coordinates *Q1*(*x1*, *y1*, 0) to *Qn*(*xn*, *yn*, 0) represent the polygon *P* orthogonally projected onto the *xy* plane *Ft*.

[0006] As to the similarity transformation process for the case  
25 where the normal vector *N* is not parallel to the *z*-axis, FIG. 12

is referred to. In such a case, the concave polygon determination section 702 finds an intersection line  $L$  of the  $xy$  plane  $Ft$  and a plane  $Fp$  which includes the polygon  $P$ . Also, found is an angle  $\alpha$  between the  $xy$  plane  $Ft$  and the plane  $Fp$ . After finding the intersection line  $L$  and the angle  $\alpha$ , the concave polygon determination section 702 rotates the vertex coordinates  $P1(x1, y1, z1)$  to  $Pn(xn, yn, zn)$  on the plane  $Fp$  about the linear intersection line  $L$  by the angle  $\alpha$ . As a result, vertex coordinate set group  $Q'1(x'1, y'1, 0)$  to  $Q'n(x'n, y'n, 0)$  are derived.

[0007] As is evident from the above description, the group of the vertex coordinates  $Q1(x1, y1, 0)$  to  $Qn(xn, yn, 0)$ , or the group of the vertex coordinates  $Q'1(x'1, y'1, 0)$  to  $Q'n(x'n, y'n, 0)$  represents a polygon  $Q$ . Described below is a process to be applied to the polygon  $Q$  represented by the group of the vertex coordinates  $Q'1$  to  $Q'n$ . Here, this process is the same to the polygon  $Q$  represented by the group of the vertex coordinates  $Q1$  to  $Qn$ , and thus is not described.

[0008] The concave polygon determination section 702 goes through a concave-convex determination process to determine whether the polygon  $Q$  is a concave polygon or not. FIG. 13 is a diagram in assistance of explaining an exemplary concave-convex determination process. Note that, although  $n$  is exemplarily 6 in the above similarity transformation process, now in the concave-convex determination process,  $n$  is presumably 4 for

convenience.

[0009] In the concave-convex determination process, the concave polygon determination section 702 first calculates 3D vectors  $V1(a1, b1, c1)$  to  $Vn(an, bn, cn)$  representing 1st to nth  
5 polygon edges of the polygon  $Q$ . As to those 3D vectors  $V1$  to  $Vn$ , their  $z$  components  $c1$  to  $cn$  are all 0. The 3D vector  $V1(a1, b1, c1)$  can be calculated from the vertex coordinates  $Q'1$  and  $Q'2$ , and is equal to  $(x'2-x'1, y'2-y'1, 0)$ . In the case where  $2 \leq i \leq n-1$ , the 3D vector  $Vi(ai, bi, ci)$  can be calculated from the  
10 vertex coordinates  $Q'1$  and  $Q'(i+1)$ , and is equal to  $(x'(i+1)-x'i, y'(i+1)-y'i, 0)$ . In the case where  $i = n$ , the 3D vector  $Vn(an, bn, cn)$  can be calculated from the vertex coordinates  $Q'n$  and  $Q'1$ , and is equal to  $(x'1-x'n, y'1-y'n, 0)$ .

[0010] After calculating all of the 3D vectors  $V1$  to  $Vn$ , the  
15 concave polygon determination section 702 calculates, sequentially, an outer product of any two vectors of polygon edges of the polygon  $Q$  intersecting with each other, i.e.,  $V1 \times V2, V2 \times V3, \dots, V(n-1) \times Vn, Vn \times V1$ . If  $z$  components of the resultant outer product vectors  $V1 \times V2, V2 \times V3, \dots, V(n-1) \times Vn, Vn \times V1$  show  
20 the same negative or positive sign, or 0, the concave polygon determination section 702 determines that the polygon  $Q$  is a convex polygon, otherwise a concave polygon.

[0011] The polygon  $Q$  is the one projected the polygon  $P$  onto the  $xy$  plane  $Ft$ . Therefore, if the polygon  $Q$  is determined as  
25 being a convex polygon, the concave polygon determination section

702 determines that the polygon  $P$  is also a convex polygon, and passes the polygon data  $Dpoly$  received from the polygon data storage section 701 to the first triangulate section 703. On the other hand, if the polygon  $P$  is determined as being a concave polygon,  
5 the polygon data  $Dpoly$  is forwarded to the second triangulate section 704.

[0012] Here, in the case where the polygon data  $Dpoly$  includes any additional information indicating the concave-convex attribute of the polygon  $P$ , the concave polygon determination  
10 section 702 does not go through the concave-convex determination process utilizing outer products, but refer to the concave-convex attribute to determine whether the polygon  $Q$ , i.e., polygon  $P$ , is a concave polygon.

[0013] To the received polygon data  $Dpoly$ , the first triangulate  
15 section 703 applies a first triangulate process so that the convex polygon  $P$  is represented by a plurality of independent triangles. In the first triangulate process, the first triangulate section 703 selects 3 sets of the vertex coordinates  $P1$ ,  $P2$ , and  $P3$  from the polygon data  $Dpoly$  to generate triangle data  $Dtri1$ .  
20 Conceptually, the convex polygon  $P$  is divided into  $\triangle P1 P2 P3$  structured by the vertex coordinates  $P1$ ,  $P2$ , and  $P3$ . In the below,  $\triangle$  denotes a triangle. For example,  $\triangle P1 P2 P3$  represents a triangle structured by the vertex coordinates  $P1$ ,  $P2$ , and  $P3$ .

[0014] Next, the first triangulate section 703 selects 3 sets  
25 of the vertex coordinates, this time,  $P1$ ,  $P3$ , and  $P4$ , to generate

triangle data  $Dtri2$ . Thereafter, when  $3 \leq i \leq n-2$ , the first  
triangulate section 703 selects in the same manner 3 sets of the  
vertex coordinate sets  $P1$ ,  $P(i+1)$ , and  $P(i+2)$  so as to generate  
triangle data  $Dtri3$  to  $Dtri(n-2)$ . Conceptually, the convex  
5 triangle  $P$  is divided into  $(n-2)$  pieces of triangles. The resultant  
 $(n-2)$  pieces of triangle data  $Dtri1$  to  $Dtri(n-2)$  are passed to  
the triangle rendering section 705. Here, when the received  
polygon data  $Dpoly$  includes additional information, the first  
triangulate section 703 ~~passes it~~ also passes it to the triangle  
10 rendering section 705.

[0015] The second triangulate section 704 retains the polygon  
data  $Dpoly$  coming from the concave polygon determination section  
702, and applies thereto a second triangulate process so that the  
concave polygon  $P$  is represented by a plurality of independent  
15 triangles. FIG. 14 shows the procedure of the second triangulate  
process. In FIG. 14, the second triangulate section 704 checks  
the vertexes of the concave polygon  $P$  for which vertex type, i.e.,  
a concave vertex or a convex vertex, and counts the number  $Nc$  of  
the concave vertexes (step S1001). Here, the concave vertex means  
20 a vertex of the concave polygon  $P$  with an interior angle exceeding  
180 degrees. Conversely, the convex vertex means a vertex with  
an interior angle smaller than 180 degrees.

[0016] In step S1001, ~~more in~~ more detail, carried out first  
is the same process as the concave-convex determination process  
25 performed by the concave polygon determination section 702. That



is, the second triangulate section 704 calculates, sequentially, an outer product of any two vectors, i.e., polygon edges, extending from one vertex  $P_i$  (where  $i = 1, 2, \dots, n$ ) of the concave polygon  $P$ . The current vertex  $P_i$  is then checked for its vertex type based on the  $z$  component of the calculated outer product, i.e., which sign the  $z$  component is showing. If the  $z$  component is showing 0, either of the vertex types is applicable to the vertex  $P_i$ .

[0017] After checking all of the  $z$  components of the outer products, the second triangulate section 704 counts the number  $N_c$  of the concave vertexes. The procedure then goes to step S1002. Here, in the below discussion, the vertex  $P_i$  determined as being the concave vertex in step S1001 is referred to as a concave vertex  $CP_i$ , otherwise a convex vertex  $VP_i$ .

[0018] In the case where the number  $N_c$  is not 0 in step S1002, the second triangulate section 704 selects one convex vertex  $VP_i$  from those others as a reference vertex  $P_b$  (step S1003). Then, the second triangulate section 704 selects, from the vertex coordinates  $P_1$  to  $P_n$ , two sets of vertex coordinates  $P_k$  and  $P_j$  (where  $k = 1, 2, \dots, n$ ,  $j = 1, 2, \dots, n$ , and  $k \neq j$ ) adjacent to the reference vertex  $P_b$ . Accordingly, the second triangulate section 704 forms a partial triangle  $\triangle P_b P_k P_j$  with the reference vertex  $P_b$ , and the vertexes  $P_k$  and  $P_j$  (step S1004).

[0019] The second triangulate section 704 then determines whether there are any other vertexes  $P_1$  to  $P_n$  in the partial triangle  $\triangle P_b P_k P_j$  (step S1005).

If determined Yes, the second triangulate section 704 regards the image data *Dimage* which will be generated by the triangle rendering section 705 as not representing the polygon *P* correctly. In other words, the partial triangle  $\triangle P_b P_k P_j$  formed in step S1004 is regarded as not being usable for rendering the polygon *P* correctly. The procedure thus returns to step S1003. The second triangulate section 704 selects again this time another convex vertex *V<sub>Pi</sub>* which is not yet selected from those others as the reference vertex *P<sub>b</sub>* (step S1003). The procedure then goes through steps S1004 and S1005.

[0020] On the other hand, if determined in step S1005 that there is no other vertexes *P<sub>1</sub>* to *P<sub>n</sub>*, the second triangulate section 704 regards the partial triangle  $\triangle P_b P_k P_j$  formed in step S1004 as being usable for rendering the polygon *P* correctly. The procedure then goes to step S1006. The second triangulate section 704 generates and retains triangle data *D<sub>tri</sub>* which represents the partial triangle  $\triangle P_b P_k P_j$  formed by the vertexes *P<sub>b</sub>*, *P<sub>k</sub>*, and *P<sub>j</sub>* (step S1006).

[0021] The second triangulate section 704 then determines whether polygon data *D<sub>poly</sub>'* can be generated from the polygon data *D<sub>poly</sub>* which is currently at hand (step S1007). To be more specific, from the polygon data *D<sub>poly</sub>*, the second triangulate section 704 eliminates the reference vertex coordinates *P<sub>b</sub>* selected in step S1003. If there ~~is~~ are no more ~~vertex~~ vertexes left, the second triangulate section 704 determines that the polygon data *D<sub>poly</sub>'*

cannot be generated so that the procedure goes to step S1010. Then, the second triangulate section 704 forwards, to the triangle rendering section 705, at least one triangle data  $Dtri$  generated in step S1006. In the case where the originally-received polygon data  $Dpoly$  includes any additional information, the second triangulate section 704 ~~passes it~~ also passes it to the triangle rendering section 705.

[0022] On the other hand, if there ~~is~~ are any ~~vertex~~ vertexes left after eliminating the reference vertex coordinates  $Pb$ , the polygon data  $Dpoly'$  is determined as being generable so that the procedure goes to step S1008. Accordingly, the second triangulate section 704 generates the polygon data  $Dpoly'$ . As such, the resultant polygon  $P'$  represented by the polygon data  $Dpoly'$  is the one formed by the vertexes  $P1$  to  $Pn$  of the polygon  $P$  except for the reference vertex  $Pb$ .

[0023] The second triangulate section 704 then sets the generated polygon data  $Dpoly'$  as the polygon data  $Dpoly$  (step S1008), and the procedure returns to step S1001. In step S1001 this time, the second triangulate section 704 counts the number  $Nc$  of the concave vertexes  $CPi$  of the polygon  $P'$ . Thereafter, the second triangulate section 704 determines if the number  $Nc$  is 0 or not, and if not 0, the procedure goes through steps S1003 to S1008 with the newly-set polygon data  $Dpoly$ .

[0024] If the number  $Nc$  is 0, the polygon  $P'$  is determined as being a convex polygon, and the second triangulate section 704

applies the first triangulate process to the polygon  $P'$  (step S1009). Assuming that the number of vertexes of the polygon  $P'$  is  $N_v$ , the second triangulate section 704 resultantly generates  $(N_v-2)$  pieces of triangle data  $D_{tri1}$  to  $D_{tri}(N_v-2)$ .

5 [0025] The second triangulate section 704 forwards, to the triangle rendering section 705, at least one triangle data  $D_{tri}$  generated in step S1006, and  $(N_v-2)$  pieces of triangle data  $D_{tri1}$  to  $D_{tri}(N_v-2)$  generated in step S1009 (step S1010). In the case where the originally-received polygon data  $D_{poly}$  includes any  
10 additional information, the second triangulate section 704 also passes it ~~also~~ to the triangle rendering section 705.

[0026] As such, the triangle rendering section 705 receives various pieces of triangle data  $D_{tri}$  from the first triangulate section 703 or the second triangulate section 704. The triangle  
15 rendering section 705 may also receive any additional information about the polygon data  $D_{poly}$ . The triangle rendering section 705 follows the additional information, specifically color information included therein, to color-fill a region formed by 3 sets of vertex coordinates  $P_r$  (where  $r = 1, 2, \dots, n$ ),  $P_s$  (where  
20  $s = 1, 2, \dots, n$ ), and  $P_t$  (where  $t = 1, 2, \dots, n$ , but  $r \neq s \neq t$ ) included in one of the received triangle data  $D_{tri}$ . Thereafter, until no triangle data  $D_{tri}$  is left at hand, the triangle rendering section 705 repeats such a rendering process as color-filling the region formed by three sets of the vertex coordinates  $P_r$ ,  $P_s$ , and  
25  $P_t$ . As a result, the image data  $D_{image}$  representing the polygon

*P* is generated in the internal memory of the triangle rendering section 705. In accordance with thus generated image data *Dimage*, the display section 706 applies a display process so that the polygon *P* is displayed on its screen.

5 [0027] As such, in the conventional rendering device *CUrend*, the triangle rendering section 705 applies the rendering process on a triangle basis to the polygon data *Dpoly*. This results in several pieces of triangle data *Dtri* from the polygon data *Dpoly*. The problem here is that the larger the number of vertexes of the  
10 polygon *P* to be rendered, the ~~more~~ greater the number of triangle data *Dtri* to be generated ~~becomes~~. As a result, the time taken for the triangle rendering section 705 to go through the rendering process becomes longer.

[0028] Especially, if the polygon *P* is a concave polygon, ~~there~~  
15 ~~requires~~ the second triangulate process (see FIG. 14) is required, which is not ~~so~~ as simple as the first triangulation process. Therefore, it takes ~~much~~ a greater amount of time for the conventional rendering device *CUrend* to render the concave polygon *P*.

20

#### SUMMARY OF THE INVENTION

[0029] Therefore, an object of the present invention is to provide rendering devices capable of rendering polygons at high speeds.

25 [0030] The present invention has the following features to

attain the object above.

[0031] A first aspect of the present invention is directed to a device for rendering a polygon which comprises: a polygon division section for generating, based on polygon data which specifies a polygon to be rendered, a plurality of partial polygon data each specifying one piece of partial polygons which are obtained by dividing the polygon; and a partial polygon rendering section for performing a rendering process, and based on the partial polygon data generated by the polygon division section, generating image data which represents an image of the polygon.

[0032] In the first aspect, each of the partial polygons include a plurality of triangles which respectively include a vertex of the polygon, and each of the triangles shares at least one edge with any at least one of the other triangles triangle included in the same partial polygon.

[0033] These and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

20

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0034] FIG. 1 is a block diagram showing the structure of a polygon rendering device *Urend* according to one embodiment of the present invention;

25 FIG. 2 is a diagram showing an exemplary structure of

the basic data structure of polygon data *Dpoly* to be processed by the polygon rendering device *Urend* of FIG. 1;

FIG. 3 is a main flowchart showing the procedure of a processor 1 of FIG. 1;

5           FIG. 4 is the first half of the flowchart showing the detailed procedure of step S36 of FIG. 3;

FIG. 5 is the second half of the flowchart showing the detailed procedure of step S36 of FIG. 3;

[0035]       FIG. 6A is a diagram showing an exemplary polygon *P* to  
10   be rendered by the polygon rendering device *Urend* of FIG. 1;

FIG. 6B is a diagram showing polygon data *Dpoly* needed for going through a rendering process to be applied to the polygon *P* of FIG. 6A;

FIG. 7A is a diagram showing a partial polygon *PP1* which  
15   is to be rendered first in the rendering process applied to render the polygon *P* of FIG. 6A;

FIG. 7B is a diagram showing the data structure of polygon data *Dpoly'* to be generated ~~firstly~~ first in step S411 of FIG. 5;

20           FIG. 8A is a diagram showing partial polygons *PP1* to *PP3* to be rendered in the rendering process applied to render the polygon *P* of FIG. 6A;

FIG. 8B is a diagram showing the data structure of polygon data *Dpoly'* to be generated ~~lastly~~ last in step S411 of FIG. 5;

25           FIG. 9 is a diagram showing the concept of perceptive

projection transformation carried out in step S37 of FIG. 3;

FIG. 10A is a diagram showing the concept of step S37 of FIG. 3 for a case where the process 1 is capable of rendering only simple rectangles;

5           FIG. 10B is a diagram showing a partial polygon  $PP$  to be rendered as a result of the process shown in FIG. 10A;

[0036]      FIG. 11 is a block diagram showing the basic structure of a conventional rendering device  $CUrend$ ;

10           FIG. 12 is a diagram in assistance of explaining similarity transformation in the rendering device  $CUrend$  of FIG. 11;

FIG. 13 is a diagram in assistance of explaining concave-convex determination in the rendering device  $CUrend$  of FIG. 11; and

15           FIG. 14 is a flowchart showing the procedure of a second triangulate process in the rendering device  $CUrend$  of FIG. 11.

#### DESCRIPTION OF THE PREFERRED EMBODIMENT

[0037]      Described first are marks  $\triangle$ ,  $\angle$ , and  $\square$  found often in  
20 the following embodiment. The mark  $\triangle$  denotes a triangle. For example,  $\triangle P1 P2 P3$  denotes a triangle formed by vertexes  $P1$ ,  $P2$ , and  $P3$ . The mark  $\angle$  denotes an angle. For example,  $\angle P1 P2 P3$  denotes an angle formed by points  $P1$ ,  $P2$ , and  $P3$ . Further, the mark  $\square$  denotes a rectangle. For example,  $\square P1 P2 P3 P4$  denotes  
25 a rectangle formed by vertexes  $P1$ ,  $P2$ ,  $P3$ , and  $P4$ .



[0038] FIG. 1 is a block diagram showing the structure of a terminal device *Dterm* to which a polygon rendering device *Urend* of one embodiment of the present invention is incorporated. In the terminal device *Dterm* of FIG. 1, the polygon rendering device  
5 *Urend* is connected to a storage device *Ustor* and a display device *Udisp* for ~~communications~~ communication therewith.

[0039] The polygon rendering device *Urend* includes a processor 1, a program memory 2, and a working area 3. The processor 1 is typically composed of a CPU (Central Processing Unit) or an MPU  
10 (Micro Processing Unit). The program memory 2 is typically composed of an ROM (Read Only Memory), and stores a computer program 21. The working area 3 is typically composed of an RAM (Random Access memory). Herein, the combination of the processor 1, the program memory 2, and the working area 3 structure not only the  
15 polygon rendering device *Urend*, but also an unwanted point elimination section and a concave polygon determination section ~~in claims~~.

[0040] In the polygon rendering device *Urend* in such a structure, the processor 1 goes through a sequence of processes in accordance  
20 with the program 21, and on the basis of polygon data *Dpoly* stored in the storage device *Ustor*, generates image data *Dimage* on the working area 3.

Here, the storage device *Ustor* stores at least one piece of polygon data *Dpoly* which specify the polygon *P* to be rendered.  
25 One piece of polygon data *Dpoly* preferably includes, as shown in

FIG. 2,  $n$  sets of vertex coordinates  $P1$  to  $Pn$  so that the polygon  $P$  is specifically rendered. Here, the vertex coordinates  $P1$  to  $Pn$  are two-dimensional (2D) or three-dimensional (3D) coordinates. If being 3D coordinates, all of the vertex coordinates  $P1$  to  $Pn$  need to be located on a single plane.

[0041] In order to define the polygon  $P$  by shape, the polygon data  $Dpoly$  also includes connection information which specifies the connection relationships among the vertexes  $P1$  to  $Pn$ . In the present embodiment, preferably, the connection information indicates in order the vertex coordinates  $P1$  to  $Pn$  in the data structure of FIG. 2. More specifically, the polygon data  $Dpoly$  includes the vertex coordinates  $P1$  to  $Pn$  in such an order that the polygon  $P$  can be derived if connecting those coordinates in one stroke in the forward direction, starting from the vertex coordinates  $P1$  and returning thereto. The polygon data  $Dpoly$  sometimes accompany various other information together with the vertex coordinates  $P1$  to  $Pn$ . Such additional information is not essential for the present invention, and will be described later only when necessary.

[0042] The display device  $Udisp$  applies a display process in accordance with the image data  $Dimage$  coming from the working area 3 so that the resultant polygon  $P$  is displayed on its screen.

Described next is the operation of the terminal device  $Dterm$  in such a structure, focusing on the operation of the polygon rendering device  $Urend$ . FIG. 3 is a main flowchart showing the

procedure of the processor 1 which is described in the program 21. Immediately after starting the program 21, the processor 1 reads out the polygon data *Dpoly* from the storage device *Ustor* for required piece(s). Here, the polygon data *Dpoly* is the one specifying the polygon *P* to be rendered. The read-out polygon data *Dpoly* is then transferred onto the working area 3 so that the polygon data *Dpoly* is retrieved (step S31). In the present embodiment, for the sake of simplicity, the processor 1 presumably retrieves one piece of polygon data *Dpoly*.

10 [0043] Thereafter, the processor 1 applies a process to the polygon data *Dpoly* on the working area 3 so as to eliminate, from the vertex coordinates *P1* to *Pn*, any vertex coordinates *Pi* (where *i* is 1, 2, ..., *n*) considered unwanted for rendering the polygon *P* (step S32). Here, ~~this step S32 corresponds to the unwanted point elimination section in claims.~~

15 [0044] As a general rule, the vertex coordinates *P1* to *Pn* each define an edge end of the polygon *P*. In some cases, however, the vertex coordinates *Pi* may happen to be on the polygon edges of the polygon *P*. Such vertex coordinates *Pi* are not used for polygon rendering, and worse yet, impair efficiency in the later processes. This is the reason why the processor 1 applies the process in S32 to eliminate any unwanted vertex coordinates. In step S32, in more detail, the processor 1 first calculates 3D vectors *Vi* (where *i* = 1, 2, ..., *n*) each representing a polygon edge of the polygon *P*. Here, the polygon data *Dpoly* presumably includes *n* sets of

20

25

3D vertex coordinates  $P1(x1, y1, z1), P2(x2, y2, z2), \dots, Pn(xn, yn, zn)$ . Here, if  $i \neq n$ , the 3D vectors  $Vi$  are directed from the vertex  $Pi$  to  $P(i+1)$ . If  $i = n$ , the 3D vector  $Vn$  is directed from the vertex  $Pn$  to  $P1$ .

5   **[0045]**   After calculating all of the 3D vectors  $Vi$ , the processor 1 calculates an outer product of any two vectors of the polygon  $P$  intersecting with each other, i.e.,  $V1 \times V2, V2 \times V3, \dots, Vi \times V(i+1), Vn \times V1$ . Here, if the absolute value of  $Vi \times V(i+1)$  is 0, it is known that the vertexes  $P(i-1), Pi$ , and  $P(i+1)$  are all  
10   positioned on the same polygon edge. Accordingly, the vertex  $Pi$  is unwanted, and thus the processor 1 eliminates it from the polygon data  $Dpoly$  on the working area 3. In the case where the polygon data  $Dpoly$  includes additional information indicating the number of vertexes, the processor 1 decrements the number by 1.  
15   If there ~~is~~ are no unwanted vertex coordinates, such as  $Pi$ , the polygon data  $Dpoly$  is left untouched on the working area 3.

**[0046]**   Note here that there is no need for such an elimination process if some special process will be applied when the polygon data  $Dpoly$  includes additional information about each of the  
20   vertexes  $P1$  to  $Pn$ , or when the polygon data  $Dpoly$  carries several of the same vertex coordinates  $P$  sequentially.

     Described below is the case where no unwanted vertex  $P1$  is eliminated in step S32. As to the case where some unwanted vertex  $Pi$  is eliminated in step S32, the same is applicable in  
25   the basic sense, and thus will not be described.

In the next step S33, the processor 1 applies, to the polygon data *Dpoly* on the working area 3, the same process as the one performed by the concave polygon determination section 702 of FIG. 11 so as to determine whether the polygon *P* specified by the polygon data *Dpoly* is a concave or convex polygon. Here, ~~this~~ step S33 corresponds to the concave polygon determination section ~~in claims.~~

[0047] When the polygon *P* is determined as being a convex polygon, the processor 1 applies the same process as the one performed by the first triangulate section 703 to generate several pieces of triangle data *Dtri* on the working area 3 (step S34). Thereafter, the processor 1 applies the same process as the one performed by the triangle rendering section 705 to generate image data *Dimage* on the working area 3 (step S35). Specifically, the image data *Dimage* is the one representing the polygon *P* which is color-filled in accordance with the color information, i.e., additional information. As such, in steps S34 and S35, if the polygon data *Dpoly* specifies the polygon *P* as being a convex polygon, the processor 1 applies the simpler first triangulate process thereto. Accordingly, the polygon rendering device *Urend* is not burdened that much to render the convex polygon *P*.

[0048] After step S35 is through, the processor 1 transfers the image data *Dimage* generated on the working area 3 to the display device *Udisp* (step S38). In accordance with the image data *Dimage*, the display device *Udisp* applies the display process so that the

polygon  $P$  is displayed on its screen.

[0049] On the other hand, if the polygon data  $Dpoly$  specifies the polygon  $P$  as being a concave polygon in step S33, the processor 1 goes through a process to divide the polygon  $P$  into a plurality of partial polygons  $PP$  (step S36). Hereinafter, such a process is referred to as a polygon division process. ~~This step~~ Step S36 corresponds to a polygon division section ~~in claims~~. Here, FIG. 4 is a flowchart showing the first half of the detailed procedure of the polygon division process, and FIG. 5 is a flowchart showing the second half thereof. Referring to FIG. 4, first, the processor 1 selects a reference vertex  $P_b$  (where  $b$  is 1, 2, ...,  $n$ ) from the vertexes  $P_1$  to  $P_n$  included in the polygon  $Dpoly$  on the working area 3 (step S401).

[0050] Also from the vertexes  $P_1$  to  $P_n$  on the working area 3, the processor 1 then selects vertexes  $P_c$  and  $P(c+1)$  (step S402). In step S402, according to the data structure of the polygon data  $Dpoly$ , the vertex  $P_c$  positions immediately after the reference vertex  $P_b$ , and the vertex  $P(c+1)$  to the vertex  $P_c$ . In such an order, the vertex  $P_c$  is to be connected next to the reference vertex  $P_b$  when connecting the vertexes in the polygon data  $Dpoly$  in the forward direction to derive the polygon  $P$  in one stroke. Similarly, the vertex  $P(c+1)$  is connected next to the  $P_c$ .

Note that the combination of these steps S401 and S402 correspond to a first selection step ~~in claims~~.

[0051] The processor 1 then determines whether or not the

following first and second conditions are satisfied (step S403).

The first condition is such a condition that  $\triangle P_b P_c P(c+1)$  formed by the reference vertex  $P_b$  and the vertexes  $P_c$  and  $P(c+1)$ , which are currently at hand, does not have any other vertex  $P_i$  therein.

5 In the first condition, "any other vertex  $P_i$ " means at least one of the vertexes  $P_1$  to  $P_n$  which is not yet selected in steps S401 and S402. That is, in step S403,  $i \neq b$ ,  $i \neq c$ ,  $i \neq c+1$ .

[0052] The second condition is such a condition that  $\angle P_b P_c P(c+1)$  formed by the current reference vertex  $P_b$  and vertexes  
10  $P_c$  and  $P(c+1)$  is smaller than 180 degrees, i.e., convex. In order to determine whether  $\angle P_b P_c P(c+1)$  is smaller than 180 degrees, the same process as the one performed by the concave polygon determination section 702 in the Background Art will do, and thus no further description is given here.

15 In the case where both of the first and second conditions are not satisfied, the processor 1 regards the current reference vertex  $P_b$  as not being appropriate for a partial polygon  $PP$ , which will be described in detail later, so that the procedure returns to step S401 to select another reference vertex  $P_b$ .

20 [0053] In step S403, if both of the first and second conditions are satisfied, the processor 1 registers, to the working area 3, the current reference vertex  $P_b$ , and vertexes  $P_c$  and  $P(c+1)$  as vertexes of the partial polygon  $PP$ . The processor 1 also increments  
25 by 1 a counter value  $Vtri$  (the counter is not shown) so that its initial value 0 is changed to 1 (step S404). Here, the value  $Vtri$

denotes how many triangles, i.e.,  $\triangle P_b P_c P(c+1)$  or  $\triangle P_b P(c+1) P(c+2)$ , the partial polygon  $PP$  currently includes.

[0054] The processor 1 then determines whether the current counter value  $Vtri$  is equal to  $(n-2)$  or not (step S405). As an example, when 3 vertexes  $P$  are selected from  $n$  vertexes  $P1$  to  $Pn$  of the polygon  $P$  to form a triangle, resultantly  $(n-2)$  pieces of triangles will be formed. Therefore, when the counter value  $Vtri$  indicates  $(n-2)$ , it means that any possible combination of vertexes  $P_b$ ,  $P(c+1)$ , and  $P(c+2)$  as to the current polygon  $P$  has been completely selected in step S406. On the other hand, if the counter value  $Vtri$  does not indicate  $(n-2)$ , it means that selection in step S406 is not yet completed.

[0055] As such, in the case of  $Vtri=(n-2)$ , the processor 1 determines that the current polygon  $P$  is now completely divided into a plurality of partial polygons  $PP$  so that the procedure goes to step S414. Here, step S414 is left for later description for easy understanding.

[0056] In the case of  $Vtri \neq (n-2)$ , the processor 1 determines that the current polygon  $P$  is not yet completely divided so that the procedure goes to step S406. In step S406, the processor 1 selects the current reference vertex  $P_b$ , and vertexes  $P(c+1)$  and  $P(c+2)$  from the vertexes  $P1$  to  $Pn$  on the working area 3. In the case that the vertex  $Pn$  has been selected as the vertex  $P(c+1)$ , the vertex  $P(c+2)$  will be the vertex  $P1$ . Herein, this step S406 corresponds to a second selection step ~~in claims~~.



[0057] In the polygon  $Dpoly$  on the working area 3, the vertex  $P(c+1)$  positions immediately after the vertex  $Pc$ , and the vertex  $P(c+2)$  after the vertex  $P(c+1)$ . In such an order, the vertex  $P(c+1)$  is to be connected next to the vertex  $Pc$  when connecting the vertexes in the polygon data  $Dpoly$  in the forward direction to derive the polygon  $P$  in one stroke. Similarly, the vertex  $P(c+2)$  is connected next to the  $P(c+1)$ .

[0058] After step S406, the processor 1 determines whether the following third and fourth conditions are satisfied (step S407).  
10 The third condition is such a condition that  $\triangle Pb P(c+1) P(c+2)$  formed by the reference vertex  $Pb$ , and the vertexes  $P(c+1)$  and  $P(c+2)$ , which are currently at hand, does not have any other vertex  $Pj$  therein. In the third condition, "any other vertex  $Pj$ " means at least one of the vertexes  $P1$  to  $Pn$  which is not yet selected  
15 in step S406. That is, in step S407,  $j \neq b$ ,  $j \neq c+1$ ,  $1 \neq c+2$ .

[0059] The fourth condition is such a condition that  $\angle Pb P(c+1) P(c+2)$  formed by the current reference vertex  $Pb$ , and vertexes  $P(c+1)$  and  $P(c+2)$  is smaller than 180 degrees, i.e., convex. In order to determine whether  $\angle Pb P(c+1) P(c+2)$  is smaller than  
20 180 degrees, the known technique as discussed above will do, and thus no further description is given here.

In step S407, if both of the third and fourth conditions are satisfied, the processor 1 additionally registers, to a predetermined region of the working area 3, the current reference  
25 vertex  $P(c+2)$  as a vertex of the partial polygon  $PP$ . The processor

1 also increments by 1 the counter value  $Vtri$  (the counter is not shown) (step S408). The case of not meeting both the third and fourth conditions is left for later description.

[0060] After step S408, the processor 1 sets the current vertex  $P(c+2)$  as a new vertex  $P(c+1)$  (step S409). This step S409 corresponds to a setting step ~~in claims~~. Then, the procedure returns to step S405, and the loop of steps S405 to S409 is repeated until the processor 1 determines as  $Vtri=(n-2)$  in step S405, or until the third and fourth conditions are determined as not being satisfied in step S407.

[0061] In step S405 as a part of the loop, when  $Vtri=(n-2)$  is satisfied, the processor 1 regards the current polygon  $P$  as being completely divided into a plurality of partial polygons  $PP$  so that the procedure goes to step S414. By the time when the polygon division process has come to step S414, the vertexes found in the working area 3 will be those forming the partial polygon  $PP$  which has been divided most recently. Specifically, the vertexes of the most-recently-divided partial polygon  $PP$  include the current vertexes  $Pb$ ,  $Pc$ , and  $P(c+1)$  only, or together with the vertex  $P(c+2)$ , at least one, if additionally registered in step S408. From those vertexes, the processor 1 generates partial polygon data  $Dpart$  (step S414), and this is the end of the polygon division process shown in FIGS. 4 and 5. That is, step S36 in FIG. 3 is now through, and the procedure goes to step S37.

[0062] The partial polygon data  $Dpart$  generated in step S414

specifies the partial polygon  $PP$ . Here, the partial polygon  $PP$  is a part of the polygon  $P$ . More specifically, the partial polygon  $PP$  is  $\triangle Pb Pc P(c+1)$  only, or together with at least one  $\triangle Pb P(c+1) P(c+2)$ . Here, if the partial polygon  $PP$  is formed by several  
5 triangles,  $\triangle Pb Pc P(c+1)$  and  $\triangle Pb P(c+1) P(c+2)$  included in the partial polygon  $PP$  share at least one polygon edge with  $\triangle Pb P(c+1) P(c+2)$  and  $\triangle Pb Pc P(c+1)$ .

[0063] In the case where both of the third and fourth conditions are not satisfied in step S407, the processor 1 regards the current  
10 vertex  $P(c+2)$  as not being appropriate for the current partial polygon  $PP$ , and also regards that one partial polygon  $PP$  is now divided from the polygon  $P$  so that the procedure goes to step S410. Here, the reason why the current vertex  $P(c+2)$  is regarded as not appropriate for the partial polygon  $PP$  will be described later.

15 [0064] By the time when the polygon division process has come to step S410, the vertexes found in the working area 3 will be those forming one partial polygon  $PP$ . Specifically, the vertexes of the partial polygon  $PP$  include the current vertexes  $Pb$ ,  $Pc$ , and  $P(c+1)$  registered in step S404 only, or together with the vertex  
20  $P(c+2)$ , at least one, if additionally registered in step S408. From those vertexes, the processor 1 generates partial polygon data  $Dpart$ , and retains it on the working area 3. Here, the partial polygon data  $Dpart$  generated in this step S410 specifies the same partial polygon  $PP$  specified by the partial polygon data  $Dpart$   
25 generated in step S414. Here, by the time step S410 has been through,

one partial polygon  $PP$  will be completely generated so that the counter value  $Vtri$  is reset to 0 as a preparation to calculate the number of triangles included in the next partial polygon  $PP$  (step S410).

5   **[0065]**     From the polygon data  $Dpoly$  on the working area 3, the processor 1 then generates polygon data  $Dpoly'$  (step S411). More specifically, from the vertex coordinates  $P1$  to  $Pn$  in the polygon data  $Dpoly$ , the processor 1 eliminates the vertexes  $Pc$ ,  $P(c+1)$ , and  $P(c+2)$  which have been selected in steps S402 and 406. It  
10   should be noted here that the vertex  $P(c+2)$  which is most recently selected, that is, the current vertex  $P(c+2)$ , is not eliminated because it will be selected as the reference vertex  $Pb$  in the later step. The reference vertex  $Pb$  is not eliminated either because it is needed to structure the polygon data  $Dpoly'$ . In order to  
15   ease the later process, the processor 1 rearranges the order of the vertex coordinates  $P$  which have not been selected, and generates the polygon data  $Dpoly'$  carrying the vertex coordinates  $P(c+2)$  to  $Pn$ , and  $Pb$  in order therein. In other words, the polygon data  $Dpoly'$  is in such a data structure that a polygon to be formed  
20   by these current vertexes can be drawn in one stroke. Any additional information included in the polygon data  $Dpoly$  may be passed to the polygon data  $Dpoly'$  as it is, or may be saved on a region of the working area 3.

**[0066]**     The processor 1 then sets the polygon data  $Dpoly'$  as  
25   the new polygon data  $Dpoly$  (step S412), and also sets the current

vertex  $P(c+2)$  as the new reference vertex  $P_b$  (step S413). Then, the procedure returns to step S402 in FIG. 4 to go through the sequence of processes.

[0067] As such, the polygon division process is described with reference to FIGS. 4 and 5. For better understanding, the polygon division process is described for a case where the polygon  $P$  specified by the polygon data  $Dpoly$  is a concave polygon as shown in FIG. 6A. Assuming here that the polygon data  $Dpoly$  specifying the concave polygon  $P$  of FIG. 6 includes vertex coordinates  $p1$  to  $P14$  in such an order as shown in FIG. 6B.

[0068] In step S401, the vertex  $P1$  is selected as the reference vertex  $P_b$ , which is indicated by a star mark in FIG. 7A. In the next step S402, the vertex  $P2$  is selected as the vertex  $P_c$ , and the vertex  $P3$  as the vertex  $P(c+1)$ . Assuming in step S403 that  $\triangle P1 P2 P3$  satisfies the first condition and  $\angle P1 P2 P3$  satisfies the second condition, in step S404, the vertexes  $P1$  to  $P3$  are registered as vertexes of the partial polygon  $PP$ , and the counter value  $Vtri$  is changed from its initial value 0 to 1.

[0069] Assuming that the vertexes  $P1$  to  $P3$  are the only vertexes so far registered for the partial polygon  $PP$ , the counter value  $Vtri$  is equal to 1. Since  $(n-2)$  is now 12, the counter value  $Vtri$  is not  $(n-2)$  in step S405. Thus, in step S406, the combination of vertexes  $P1$ ,  $P3$ , and  $P4$  will be selected as the combination of the reference vertex  $P_b$ , and the vertexes  $P(c+1)$  and  $P(c+2)$ . Assuming in step S407 that  $\triangle P1 P3 P4$  satisfies the third condition

and  $\angle P1 P3 P4$  satisfies the fourth condition, the vertex  $P4$  is additionally registered as a vertex of the partial polygon  $PP$  in step S408, and the counter value  $Vtri$  is changed from 1 to 2. In the next step S409, the vertex  $P4$  which is the current vertex  $P(c+2)$  is set as the new vertex  $P(c+1)$ .

[0070] If the counter value  $Vtri$  is determined as not yet indicating  $(n-2)$  in step S405, the procedure again goes to step S406. Since the current reference vertex  $Pb$  and the vertex  $P(c+1)$  are the vertexes  $P1$  and  $P4$ , respectively, selected in step S406 as the vertex  $P(c+2)$  is the vertex  $P5$ . Assuming in step S407 that  $\triangle P1 P4 P5$  satisfies the third condition and  $\angle P1 P4 P5$  satisfies the fourth condition, in step S408, the vertex  $P5$  is additionally registered as a vertex of the partial polygon  $PP$ , and the counter value  $Vtri$  is changed from 2 to 3. In the next step S409, the vertex  $P5$  which is the current vertex  $P(c+2)$  is set as the new vertex  $P(c+1)$ .

[0071] If the counter value  $Vtri$  is determined as not yet indicating  $(n-2)$  in step S405, selected in step S406 as the vertex  $P(c+2)$  is the vertex  $P6$ . Assuming in step S407 that  $\triangle P1 P5 P6$  satisfies the third condition and  $\angle P1 P5 P6$  satisfies the fourth condition, in step S408, the vertex  $P6$  is additionally registered as a vertex of the partial polygon  $PP$ , and the counter value  $Vtri$  is changed to 4. In the next step S409, the vertex  $P6$  is set as the new vertex  $P(c+1)$ .

[0072] If the counter value  $Vtri$  is determined as not yet

indicating  $(n-2)$  in step S405, selected in step S406 as the vertex  $P(c+2)$  is the vertex  $P7$ . Here, if  $\angle P1 P6 P7$  is exceeding 180 degrees, i.e., concave, the fourth condition is not satisfied. Therefore, the processor 1 regards the current vertex  $P(c+2)$ , i.e.,  
5 the vertex  $P7$ , is not appropriate as the vertex of the partial polygon  $PP$ . The reason why the vertex  $P7$  is considered not appropriate is, if  $\angle P1 P6 P7$  as  $\angle P6 P(c+1) P(c+2)$  is concave, the line segment from the vertex  $P6$  to  $P7$  goes backward with respect to the line segment from the vertex  $P5$  to  $P6$  so that the partial  
10 polygon  $PP$  cannot be correctly rendered in the later step S37.  
~~With~~ For the same reason, when the third condition is not satisfied, the vertex  $P(c+2)$  is determined as not being appropriate as the vertex of the partial polygon  $PP$ .

[0073] As such, when both of the third and fourth conditions  
15 are determined as not being met, the processor 1 determines that one partial polygon  $PP$  is now divided from the polygon  $P$  so that the procedure goes to step S410. In step S410 in this example, the polygon data  $Dpart$  including the vertex coordinates  $P1$  to  $P6$  is generated and retained. Further, in step S410, the counter  
20 value  $Vtri$  which is indicating 4 is reset to 0. Here, for convenience, the partial polygon data  $Dpart$  which is currently generated is referred to as partial polygon data  $Dpart1$ . The partial polygon data  $Dpart1$  specifies a partial polygon  $PP1$  (shown with hatched lines descending toward left in FIG. 7A) formed by  
25 the vertexes  $P1$  to  $P6$ .

[0074] Here, the partial polygon  $PP1$  is structured by  $\triangle P1 P2 P3$ ,  $\triangle P1 P3 P4$ ,  $\triangle P1 P4 P5$ , and  $\triangle P1 P5 P6$ , all of which share the same reference vertex  $Pb(=P1)$ . Moreover,  $\triangle P1 P2 P3$  share a polygon edge  $P1 P3$  with  $\triangle P1 P3 P4$ . Other than those,  $\triangle P1 P3 P4$ ,  $\triangle P1 P4 P5$ , and  $\triangle P1 P5 P6$  are also included in the partial polygon  $PP1$ , and share at least one polygon edge with ~~any of~~ at least one other triangles triangle.

[0075] In step S411, as already described, except for the vertexes  $Pc$  and  $P(c+1)$ , and the current vertex  $P(c+2)$ , any other vertex(es)  $P(c+2)$  are eliminated from the vertex coordinates  $P1$  to  $Pn$ . Accordingly, after the vertex coordinates  $P2$  to  $P5$  are eliminated from the polygon data  $Dpoly$  on the working area 3, the vertex coordinates  $P$  are rearranged in order so that the polygon data  $Dpoly'$  carrying 10 vertex coordinates  $P6$  to  $P14$  in order is generated as shown in FIG. 7B. Then in step S412, the polygon data  $Dpoly'$  is set as the new polygon data  $Dpoly$ . Then in step S413, the vertex  $P6$  is set as the reference vertex  $Pb$ .

[0076] In the case where the vertex  $P6$  is the reference vertex  $Pb$ , the third and fourth conditions remain satisfied until the vertex  $P11$  becomes the vertex  $P(c+1)$  and the vertex  $P12$  the vertex  $P(c+2)$  (step S407). Accordingly, generated and retained in step S410 is partial polygon data  $Dpart2$  by which such a partial polygon  $PP2$  (shown with hatched lines descending toward right) as shown in FIG. 8A is specified. In step S411, after eliminating the vertex coordinates  $P7$  to  $P10$  from the polygon data  $Dpoly$  on the working



area 3, the vertex coordinates  $P$  are rearranged in order. As a result, generated is the polygon data  $Dpoly'$  carrying, as shown in FIG. 8B, 6 sets of vertex coordinates  $P11$  to  $P14$ ,  $P1$ , and  $P6$  in order therein. This polygon data  $Dpoly'$  is then set as the new polygon data  $Dpoly$  in step S412.

[0077] Referring to FIG. 8A, in step S413, after the vertex  $P11$  is set as the reference vertex  $Pb$ , the procedure of the polygon division process returns to step S402. In step S402, the vertex  $S12$  is selected as the vertex  $Pc$ , and the vertex  $P13$  as the vertex  $P(c+1)$ . Here, assuming in step S403 that  $\triangle P11 P12 P13$  satisfies the first condition and  $\angle P11 P12 P13$  satisfies the second condition, in step S404, the vertexes  $P11$  to  $P13$  are registered, and the counter value  $Vtri$  is updated to 1.

[0078] Assuming that the vertexes  $P11$  to  $P13$  are the only vertexes so far registered for the partial polygon  $PP$ , the counter value  $Vtri$  is equal to 1. Since  $(n-2)$  is now 4, the counter value  $Vtri$  is not  $(n-2)$  in step S405. Thus, in step S406, the combination of vertexes  $P11$ ,  $P13$ , and  $P14$  will be selected as the combination of the reference vertex  $Pb$ , and the vertexes  $P(c+1)$  and  $P(c+2)$ . Assuming in step S407 that  $\triangle P11 P13 P14$  satisfies the third condition and  $\angle P11 P13 P14$  satisfies the fourth condition, the vertex  $P14$  is additionally registered as a vertex of the partial polygon  $PP$  in step S408, and the counter value  $Vtri$  is changed to 2. In the next step S409, the vertex  $P14$  which is the current vertex  $P(c+2)$  is set as the new vertex  $P(c+1)$ .

[0079] If the counter value  $Vtri$  is determined as not yet indicating  $(n-2)$  in step S405, the procedure again goes to step S406. Since the current reference vertex  $Pb$  and the vertex  $P(c+1)$  are the vertexes  $P11$  and  $P14$ , respectively, and since the vertex  
5  $P1$  follows immediately after the vertex  $P14$  in the current polygon data  $Dpoly$ , selected in step S406 as the vertex  $P(c+2)$  is the vertex  $P1$ . Assuming in step S407 that  $\triangle P11 P14 P1$  satisfies the third condition and  $\angle P11 P14 P1$  satisfies the fourth condition, in step S408, the vertex  $P1$  is additionally registered, and the counter  
10 value  $Vtri$  is updated to 3. In the next step S409, the vertex  $P1$  which is the current vertex  $P(c+2)$  is set as the new vertex  $P(c+1)$ .

[0080] If the counter value  $Vtri$  is determined as not yet indicating  $(n-2)$  in step S405, selected in step S406 as the vertex  
15  $P(c+2)$  is the vertex  $P6$ , which follows immediately after the vertex  $P1$ . Assuming in step S407 that  $\triangle P11 P1 P6$  satisfies the third condition and  $\angle P11 P1 P6$  satisfies the fourth condition, in step S408, the vertex  $P6$  is additionally registered, and the counter value  $Vtri$  is updated to 4. In the next step S409, the vertex  
20  $P6$  is set as the new vertex  $P(c+1)$ .

[0081] Then, when the counter value  $Vtri$  is determined as being  $(n-2)$  in step S405, the processor 1 regards the partial polygon  $PP$  as being perfectly divided from the polygon  $P$ . The procedure then goes to step S414. In step S414, generated and retained is  
25 partial polygon data  $Dpart$  including the vertex coordinates  $P11$

to *P14*, *P1*, and *P6* which are found in the working area 3. For convenience, the resultant partial polygon data *Dpart* is referred to as partial polygon data *Dpart3*. The partial polygon data *Dpart3* specifies a partial polygon *PP3* which is indicated by the double-hatched area in FIG. 8B.

[0082] Described above is the specific example of the polygon division process by referring to FIGS. 6 to 8. In the example, generated on the working area 3 are three pieces of partial polygon data *Dpart1* to *Dpart3*. After generating such partial polygon data, the procedure goes to step S37 of FIG. 3.

[0083] In step S37, the processor 1 selects one partial polygon data *Dpart* generated in step S36, and then generates partial image data which represents the partial polygon *PP* on the working area 3 in accordance with color information, i.e., additional information of the polygon data *Dpoly*. To be more specific, the partial image data is the one defining the partial polygon *PP* by shape, and representing the partial polygon *PP* which is filled by the color specified by the color information. The processor 1 applies the process as described above to any other partial polygon data *Dpart* so that the image data *Dimage* is generated on the working area 3 which defines the polygon *P* by shape, and represents the polygon *P* color-filled in accordance with the color information (step S37). Here, this step S37 corresponds to a partial polygon rendering section ~~in claims~~.

[0084] Here, as shown in FIG. 9, in step S37, the processor

1 may apply a perspective projection transformation process with respect to the partial polygon data *Dpart* generated in step S36. Specifically, in the perspective projection transformation process, the partial polygon data *Dpart* is subjected to coordinate transformation so that the partial polygons *PP* are projected onto a screen *SR* perpendicular to the vector representing the line of sight including a predetermined viewpoint on the 3D space. As a result, displayed on the screen *SR* is a polygon *P'*.

After step S37 is through, the processor 1 transfers the image data *Dimage* generated on the working area 3 to the display device *Udisp* (step S38). In accordance with the image data *Dimage*, the display device *Udisp* performs the display process so that the polygon *P* is displayed on its screen.

[0085] As described above, according to the polygon rendering device *Urend* of the present embodiment, the polygon division process (step S36) divides the concave polygon *P* into the partial polygons *PP*. Accordingly, in step S37, the process of rendering partial polygons is carried out on the partial polygon *PP* basis, and resultantly generated is the image data *Dimage* representing the concave polygon *P*. Therefore, compared with the conventional rendering process applied to the concave polygon *P*, the amount of data, especially the number of vertex coordinates *P* can be reduced to a greater degree in the process of rendering partial polygons. Accordingly, the concave polygon *P* can be rendered at higher speeds.

[0086] Here, in the above, steps S36 and S37 are carried out

with respect to the polygon data *Dpoly* specifying the polygon *P* as being a concave polygon. This is not restrictive, and those steps may be applied to the polygon data *Dpoly* specifying the polygon *P* as being a convex polygon.

5 | [0087] Also in the above discussion, the processor 1 reads out the polygon data *Dpoly* in step S31 from the storage device *Ustor* which is internally provided in the terminal device *Dterm* to the working area for the later processes. Alternatively, the processor 1 may transfer the polygon data *Dpoly* coming over  
10 | communications paths typified by the networks and buses to the working area 3, and carry out steps S32 to S38 with respect to the polygon data *Dpoly*. That is, the polygon rendering device *Urend* does not necessarily require the storage device *Ustor*.

[0088] Further, in the above, the processor 1 transfers the  
15 | image data *Dimage* in step S38 from the working area 3 to the display device *Udisp* which is internally provided in the terminal device *Dterm*. This is not restrictive, and the processor 1 may transfer the image data *Dimage* to the display device which is externally provided to the terminal device *Dterm* over the communications paths.  
20 | That is, the polygon rendering device *Urend* does not necessarily require the storage device *Ustor*.

| [0089] Also in the above discussion, the polygon data *Dpoly* presumably includes the vertex coordinates *P1* to *Pn* in such an order that the polygon *P* can be rendered in one stroke. Here,  
25 | if the polygon data *Dpoly* does not carry the vertex coordinates

*P* in such an order, the processor 1 may rearrange the vertex coordinates *P*<sub>1</sub> to *P*<sub>*n*</sub> in such an order in accordance with the connection information, i.e., additional information, before going to step S36.

5 | [0090] Also in the above discussion, if the partial polygon *PP* is structured by a plurality of triangles, the partial polygon data *Dpart* in the storage device *Ustor* includes, together with the reference vertex *Pb*, vertex coordinates *P* which ~~specifies~~ specify a partial polygon *PP* structured by a triangle  $\triangle Pb Pc P(c+1)$ ,  
10 | and at least one triangle  $\triangle Pb P(c+1) P(c+2)$ . In some cases, however, the processor 1 may be capable of rendering only simple rectangles due to its computing power. If so, as the partial polygon data *Dpart*, the processor 1 may generate data including, together with the reference vertex *Pb*, vertex coordinates *P* which ~~specifies~~  
15 | specify a partial polygon *PP* structured by a rectangle  $\square Pb Pc P(c+1) Pb$ , and at least one rectangle  $\square Pb P(c+1) P(c+2) Pb$ . If the processor 1 carries out the process of rendering partial polygons (step S37) in accordance such partial polygon data *Dpart*,  
20 | formally, resultantly rendered will be the rectangles  $\square Pb Pc P(c+1) Pb$ , and  $\square Pb P(c+1) P(c+2) Pb$  as shown in FIG. 10A. Since these rectangles share the same reference vertex *Pb*, such a partial polygon *PP* as shown in FIG. 10B can be resultantly rendered.

[0091] While the invention has been described in detail, the foregoing description is in all aspects illustrative and not  
25 | restrictive. It is understood that numerous other modifications

and variations can be devised without departing from the scope of the invention.

# ABSTRACT OF THE DISCLOSURE

A polygon rendering device ~~Urend~~ carries out a polygon division process, ~~in step S36,~~ for generating, based on polygon data which specifies a polygon to be rendered, a plurality of partial  
5 polygon data each specifying one piece of partial polygons which are obtained by dividing the polygon. Then, ~~in step S37,~~ a rendering process is performed based on the generated partial polygon data ~~generated in step S36~~ so as to generate image data which represents an image of the polygon. Here, each of the partial  
10 polygons includes a plurality of triangles which respectively include a vertex of the polygon, and each of the triangles included in each of the partial polygons shares at least one edge with ~~any~~  
at least one of the triangles other triangle included in the same partial polygon. In such a manner, the polygon rendering device  
15 ~~Urend~~ can render polygons at high speeds.